

Utility Trailers, Snowmobile Trailers, Boat Trailers, Stock Trailers, Log Splitters & Campers

USA TRAIL®



USA TRAIL is Approved for Highway Speed Use

SIZE	PRODUCT CODE	LOAD RANGE	MTD DIA.	MTD WIDTH	RIM WIDTH	MAX LOAD CAPACITY	MAX PSI	TIRE WEIGHT	TREAD DEPTH (32nds)
4.80 - 8	519056	LRB	17.1	5.1	3.75	590	60	6.7	6
4.80 - 8	519058	LRC	17.4	5.1	3.75	745	90	8.1	6
5.70 - 8	519086	LRB	19.2	6.0	3.75	715	50	9.8	10
5.70 - 8	519087	LRC	18.8	6.0	3.75	910	75	11.3	10
5.70 - 8	519088	LRD	18.9	6.1	3.75	1075	100	12.3	10
16.5 x 6.5 - 8	519296	LRB	16.6	6.4	5.38	620	45	8.9	7
16.5 x 6.5 - 8	519297	LRC	16.2	6.6	5.38	795	70	10.9	7
16.5 x 6.5 - 8	519298	LRD	16.3	6.7	5.38	915	90	10.7	7
18.5 x 8.5 - 8	519471	LRB	18.0	8.4	7.00	770	35	13.7	10
18.5 x 8.5 - 8	519472	LRC	17.7	8.5	7.00	940	50	15.4	10
6.90 - 9	519572	LRC	22.0	7.1	4.50	1120	60	13.0	10
20.5 x 8.0 - 10	519141	LRB	21.0	8.4	6.00	905	35	15.8	10
20.5 x 8.0 - 10	519142	LRC	20.7	8.5	6.00	1105	50	17.6	10
20.5 x 8.0 - 10	519143	LRD	20.5	8.6	6.00	1330	70	17.8	10
20.5 x 8.0 - 10	519144	LRE	20.9	8.7	6.00	1535	90	18.7	10
20.5 x 8.0 - 10	519145	LRF	20.5	8.6	6.00	1675	105	20.4	10
4.80 - 12	519062	LRB	21.0	5.0	4.00	780	60	9.6	8
4.80 - 12	519063	LRC	21.3	5.1	4.00	990	90	10.3	8
5.30 - 12	519076	LRB	21.8	5.3	4.00	840	55	10.3	8
5.30 - 12	519077	LRC	22.1	5.3	4.00	1045	80	11.5	8
ST175/80D13	519160	LRB	24.7	6.7	4.50	1100	35	16.1	10
ST175/80D13	519161	LRC	25.0	6.7	4.50	1360	50	17.1	10
ST205/75D14	519310	LRB	26.6	8.1	5.50	1430	35	21.1	10
ST205/75D14	519300	LRC	26.9	8.1	5.50	1760	50	21.3	10
ST215/75D14	519315	LRC	26.5	8.3	6.00	1870	50	24.9	10
ST205/75D15	519400	LRC	27.1	8.0	5.50	1820	50	24.1	10
ST225/75D15	519410	LRC	28.1	8.9	6.00	2150	50	28.6	10
ST225/75D15	519412	LRD	28.6	9.0	6.00	2540	65	33.6	10

HIGHWAY SPEED TRAILER TIRES:

USA Trail, Sure Trail, Radial Trail

Approved for over-the-highway use, these tires comply with U.S. Department of Transportation requirements. Their long-lasting, wrap-around tread provides sure cornering and safe travel.



Utility Trailers, Snowmobile Trailers, Boat Trailers, Stock Trailers, Log Splitters & Campers

SURE TRAIL®

SURE TRAIL LT®

EXTRA GRIP



SURE TRAIL is Approved for Highway Speed Use

SURE TRAIL®

SIZE	PRODUCT CODE	LOAD RANGE	MTD DIA.	MTD WIDTH	RIM WIDTH	MAX LOAD CAPACITY	MAX PSI	TIRE WEIGHT	TREAD DEPTH (32nds)
4.80 - 8	519054	LRB	16.7	4.9	3.75	590	60	6.1	6
4.80 - 8	519057	LRC	16.7	5.0	3.75	745	90	7.6	6
5.70 - 8	519060	LRB	18.5	5.8	3.75	715	50	8.4	7
5.70 - 8	519061	LRC	18.5	5.9	3.75	910	75	9.2	7
4.80 - 12	519065	LRB	20.7	4.8	4.00	780	60	8.5	6
4.80 - 12	519066	LRC	20.9	4.9	4.00	990	90	9.5	6
5.30 - 12	519070	LRB	21.4	5.3	4.00	840	55	8.9	7
5.30 - 12	519071	LRC	21.7	5.4	4.00	1045	80	10.2	7
ST165/80D13	519156	LRC	23.4	6.1	4.50	1230	50	12.9	10
ST175/80D13	519158	LRB	23.7	6.2	4.50	1100	35	13.4	10
ST175/80D13	519159	LRC	23.8	6.2	4.50	1360	50	14.1	10
ST185/80D13	519165	LRC	24.5	6.6	4.50	1480	50	15.1	10
ST185/80D13	519166	LRD	23.2	6.8	4.50	1730	65	17.6	10
ST195/75D14	519305	LRB	24.6	7.1	5.50	1320	35	16.3	10
ST195/75D14	519306	LRC	24.9	7.2	5.50	1610	50	17.2	10
ST205/75D14	519312	LRB	25.4	7.5	5.50	1430	35	16.7	10
ST205/75D14	519311	LRC	25.6	7.5	5.50	1760	50	17.9	10
ST215/75D14	519316	LRC	26.2	8.0	6.00	1870	50	18.9	10
ST205/75D15	519399	LRB	27.1	7.5	5.50	1480	35	17.7	8
ST205/75D15	519401	LRC	27.1	7.6	5.50	1820	50	20.3	8
ST225/75D15	519411	LRC	27.1	8.7	6.00	2150	50	22.4	10
ST225/75D15	519413	LRD	27.6	8.6	6.00	2540	65	27.5	10

SURE TRAIL LT®

7 - 14.5LT	519504	LRD	26.5	8.1	6.00	1870	70	23.7	10
8 - 14.5LT	5195031	LRF	28.3	8.2	6.00	2790	100	30.5	10
7.00 - 15LT	5196111	LRD	29.3	7.8	5.50	2040-S 1820-D	60	33.4	14
7.50 - 16LT	5196051	LRE	31.8	8.7	6.00	2780-S 2440-D	75	39.3	14

EXTRA GRIP

5.70 - 8	519886	LRB	18.6	5.8	3.75	715	50	10.8	10
----------	--------	-----	------	-----	------	-----	----	------	----

S=Single D=Dual

Utility Trailers, Snowmobile Trailers, Boat Trailers, Stock Trailers, Log Splitters & Campers

RADIAL TRAIL



RADIAL TRAIL is Approved for Highway Speed Use

RADIAL TRAIL

SIZE	PRODUCT CODE	LOAD RANGE	MTD DIA.	MTD WIDTH	RIM WIDTH	MAX LOAD CAPACITY	MAX PSI	TIRE WEIGHT	TREAD DEPTH (32nds)
ST145/R12	5151291	LRD	21.1	5.7	4.00	1220	65	15.0	8
ST175/80R13	5198121	LRC	24.1	6.7	4.50	1360	50	16.5	10
ST205/75R14	5198131	LRC	26.1	8.0	5.50	1760	50	23.8	10
ST215/75R14	5198141	LRC	26.8	8.2	6.00	1870	50	25.1	10
ST205/75R15	5198151	LRC	27.2	8.0	5.50	1820	50	25.6	10
ST225/75R15	5198161	LRC	28.2	8.8	6.00	2150	50	28.5	10
ST225/75R15	5198171	LRD	28.3	8.8	6.00	2540	65	29.6	10
ST225/75R15	5198221	LRE	28.2	9.0	6.00	2830	80	30.5	10
ST235/85R16	5198231	LRD	31.9	9.1	6.00	3200 - S 2835 - D	65	40.9	16
ST235/85R16	5193411	LRF	31.9	9.1	6.00	3960 - S 3520 - D	95	40.4	16
ST245/75R16	5198241	LRD	30.5	9.3	6.00	3000 - S 2680 - D	65	42.3	16

S=Single D=Dual

HIGHWAY SPEED TRAILER

Airport Support Equipment

GROUND FORCE GSE:

Our Ground Force tires combine extra tread depth and the exclusive CT-4 tread compound to set a new standard of durability and wear in the ground support industry. Each tire features a built-in rim guard for maximum wheel protection.



GROUND FORCE GSE™

A

B



GROUND FORCE GSE™

SIZE	PRODUCT CODE	PLY	MTD DIA.	MTD WIDTH	RIM WIDTH	MAX LOAD CAPACITY @ 10MPH	MAX PSI	TIRE WEIGHT	TREAD DEPTH (32nds)
4.80 - 8 (TT) A	52N242	8	16.5	4.8	3.75	1160	145	10.4	11
5.70 - 8 (TT) A	52N208	8	18.4	5.9	3.75	1470	120	12.5	11
6.90 - 9 (TT) A	52N260	10	21.6	6.8	4.00	2200	125	23.3	24
6.50 - 10 (TL) A	52N394	6	23.2	7.1	5.00	1895	70	24.0	11
6.50 - 10 (TT) A	52N263	10	23.2	7.1	5.00	2535	115	28.5	24
9.00 - 10 (TT) B	52N221	10	27.2	9.7	6.00	3720	85	34.4	9
9.00 - 10 (TT) B	52N209	16	26.4	10.0	6.00	4880	135	37.8	9
175/80D13 (TL) A	52N3T9	8	23.7	6.1	5.00	3920	100	26.9	24

INDUSTRIAL